

181 系列充油式压力表

181 Liquid Filled Pressure Gauges

Description

181 系列是专为极端环境或高纯度设备而设计，具有 SS304 表壳和 SS316 内接，可用于大多数腐蚀性环境，振动和脉动环境，食品，供水，医疗等。

181 series are designed for critical environment or high pure devices with long durability, it has SS304 housing and SS316 internals, can be used in most corrosive atmospheres, vibration and pulsation environments.




181A

Material Feature

指针 Pointer:	铝 Aluminium	焊接类型 Welding Type:	氩弧焊 Argon-arc Welding
机芯 Movement:	不锈钢 SS304	外壳 Case:	不锈钢 SS304
接头 Connection:	不锈钢 SS316	表圈 Ring:	不锈钢 SS304
精度 Accuracy:	1.6%/1.0%*	螺纹尺寸 Thread Size:	1/8", 1/4", M14
表面 Window:	聚碳酸酯 Polycarbonate	弹簧管 Bourdon Tube:	不锈钢 SS316L
填充液 Filling Liquid:	甘油 Glycerine	压力范围 Pres. Range:	VAC~9PSI~15000PSI
*1.0%的精度可定制 *1.0% accuracy is available when required			

Dimensions



Code	Dia (mm)	Sizes (mm)					
		A	B	C	D	E	F
B181	50	57.5	50.5	6.5	22.0	14.0	26.0
C181	63	68.0	61.0	6.5	22.0	14.0	26.0

Main Mount type



Bottom Mount



Back Mount



Solder interface

